

Proportional pressure relief valve, pilot operated, increasing characteristic curve KBVS.0A



HAD7893

- ▶ Size 0
- ▶ Series A
- ▶ Maximum working pressure 420 bar
- ▶ Maximum flow 25 l/min

Features

- ▶ Cartridge valve
- ▶ R/C019E mounting cavity
- ▶ Pilot operated proportional valve for limiting system pressure
- ▶ Suitable for mobile applications
- ▶ Actuated by proportional solenoid with central thread and removable coil
- ▶ Rotatable solenoid coil
- ▶ In case of power failure, minimum pressure is set
- ▶ Setpoint pressure characteristic curve can be finely calibrated using control electronics externally

Contents

Type code	2
Preferred types	2
Functional description	3
Technical data	4
Characteristic curves	7
Permissible working range	8
Dimensions	10
Mounting cavity	11
Available individual components	12
Related documentation	12

Type code

01	02	03	04	05	06	07	08	09	10	11	12
KBVS		0	A	A	/	F	C		V		*

01	Proportional pressure relief valve, pilot operated	KBVS
----	--	-------------

Pressure stage¹⁾

02	Up to 210 bar (on request)	L
	Up to 250 bar (on request)	N
	Up to 315 bar (on request)	P
	Up to 350 bar (on request)	R
	Up to 420 bar	T

03	Size 0	0
----	--------	----------

04	If setpoint = 0, minimum pressure is set	A
----	--	----------

05	Series	A
----	--------	----------

06	R/C019E mounting cavity (see page 11)	F
----	---------------------------------------	----------

07	Proportional solenoid, switching in oil	C
----	---	----------

Supply voltage

08	Control electronics 12 V DC	G12
	Control electronics 24 V DC	G24

Electrical connection²⁾

09	Device connector according to DIN EN 175301-803	K4
	Device connector 2-pin, DT 04-2P (DEUTSCH)	K40
	Device connector 2-pin, Junior Timer (AMP)	C4

Sealing material

10	FKM (fluorocarbon rubber), other seals on request	V
----	---	----------

11	Standard variant	No code
	Preferred variant 24 V/800 mA	-8

12	Further details in plain text	*
----	-------------------------------	----------

Preferred types

Type	Material number
KBVST0AA/FCG24K40V-8	R901444686
KBVST0AA/FCG24C4V-8	R901488221

¹⁾ Other pressure stages on request

²⁾ Plug-in connectors are not included in the scope of delivery and must be ordered separately, see data sheet 08006.

Functional description

General

Valves of type KBVS are pilot operated proportional pressure relief valves of spool design and are used to limit the pressure in hydraulic systems. Their primary components are a screw-in proportional pilot control valve (1) and the main valve (2). These valves can be used for infinitely adjusting the pressure to be limited depending on the setpoint. Minimum pressure is set in case of power failure or if the setpoint value is 0.


Basic principle

To proportionally increasing the system pressure, a setpoint is specified using the control electronics. Depending on this setpoint, the electronics power the solenoid coil, which uses the pilot control valve (1) and main valve (2) to actually set the pressure at port P. ($p_{\max}$ = maximum setpoint; $p_{\min}$ = setpoint of 0)

Notice

Occurring tank pressures (port T) are added to the set value at port P.

▼ Type KBVS.0A..



Technical data

General		
Weight	kg	0.54
Installation position		Any – if it is ensured that no air can collect upstream the valve. Otherwise we recommend suspend installation of the valve.
Ambient temperature range	°C	–40 to +120 (see pages 8 and 9)
Storage temperature	°C	–20 to +80

Environmental testing

Vibration test in accordance with DIN EN 60068-2/IEC 60068-2/two axes (X/Y)		
DIN EN 60068-2-6: 05/96	Sinusoidal vibration	10 cycles (5 Hz to 2000 Hz back to 5 Hz) with logarithmic sweep rate of 1 oct/min, 5 to 57 Hz, amplitude 1.6 mm (p–p), 57 to 2000 Hz, amplitude 10 g
IEC 60068-2-64: 05/93	Vibration (random) and broadband noise	20 to 2000 Hz, amplitude 0.1 g ² /Hz (14 g RMS/30 g peak), testing time 24 h
DIN EN 60068-2-27: 03/95	Shock	Half sine 15 g/11 ms; 3× in positive; 3× in negative direction (6 single shocks total)
DIN EN 60068-2-29: 03/95	Continuous shock	Half sine 15 g/11 ms; 1000× in positive; 1000× in negative direction (2000 single shocks total)
Indication per axis		
Climate test in accordance with DIN/EN 60068-2/IEC 60068-2 (environmental audit)		
DIN EN 60068-2-1: 03/95	Storage temperature	–40 °C, dwell time 16 h
DIN EN 60068-2-2: 08/94		+110 °C, dwell time 16 h
DIN EN 60068-2-1: 03/95	Cold test	2 cycles, –25 °C, dwell time 2 h
DIN EN 60068-2-2: 08/94	Dry heat test	2 cycles, +120 °C, dwell time 2 h
IEC 60068-2-30: 1985	Humid heat, cyclical	Variant 2/ +25 °C to +55 °C 93 % to 97 % RH, 2 cycles of 24 h
Salt spray test in accordance with DIN 50021		
	h	720
→ Varnishing generally not necessary. If varnishing, note reduced radiation output.		

Notice

For applications outside these values, please consult us!

Hydraulic			
Maximum working pressure ¹⁾	Port P	bar	420
Maximum return flow pressure	Port T	bar	210
Maximum set pressure ²⁾			See setpoint pressure characteristic curve on page 7
Minimum set pressure when setpoint is 0			See characteristic curve on page 7
Maximum flow		l/min	25
Leakage		ml/min	< 450 (at $\Delta p = 250$ bar; closed pilot control valve and HLP46, $\vartheta_{oil} = 40$ °C)
Hydraulic fluid			See table below
Hydraulic fluid temperature range		°C	-40 to +80
Viscosity range		mm ² /s	5 to 400 (preferably 10 to 100)
Maximum admissible degree of contamination of hydraulic fluid Cleanliness level per ISO 4406 (c)			Class 20/18/15 ³⁾
Load cycles			2 m
Hysteresis ⁴⁾			< 4 % of maximum set pressure
Turnover voltage ⁴⁾			< 0.5 % of maximum set pressure
Responsiveness ⁴⁾			< 0.5 % of maximum set pressure
Setpoint pressure characteristic curve tolerance	Setpoint 100 %		< 2 % of maximum set pressure
	Setpoint 0		< 5 % of maximum set pressure
Step response ($T_u + T_g$) 0 → 100 % or 100 % → 0		ms	100 (depending on system)

Hydraulic fluid

Hydraulic fluid		Classification	Suitable sealing materials	Standards	Data sheet
Mineral oils		HL, HLP	FKM	DIN 51524	90220
Environmentally acceptable	insoluble in water	HEES	FKM	ISO 15380	90221
	soluble in water	HEPG	FKM	ISO 15380	90221

Notice

- Further information and details on using other hydraulic fluids are available in the above data sheets or on request.
- Restrictions are possible with the technical valve data (temperature, pressure range, service life, maintenance intervals, etc.)!
- The flash point of the hydraulic fluid used must be 40 K above the maximum solenoid surface temperature.
- **Environmentally acceptable:** If environmentally acceptable hydraulic fluids are used that are also zinc-dissolving, there may be an accumulation of zinc.

1) The maximum working pressure is the aggregate of set pressure and return flow pressure!
 2) The valves come preset. Changing the settings voids the warranty.

3) Cleanliness levels specified for the components must be maintained in the hydraulic systems. Effective filtration prevents malfunctions and simultaneously extends the service life of the components.
 4) Measured with analog amplifier of type RA2-1/10, see data sheet 95230 (PWM = 300 Hz).

Electric					
Voltage type			DC voltage		
Supply voltage		V	12 DC	24 DC	"-8"/24 DC
Maximum solenoid current		mA	1760	1200	800
Coil resistance	Cold value at 20 °C	Ω	2.3	4.8	11.5
	Maximum warm value	Ω	3.8	7.9	18.9
Duty cycle		%	See characteristic curve on pages 8 and 9 ⁵⁾		
Maximum coil temperature ⁶⁾		°C	150		
Type of protection according to ISO 20653	Connector version "K4"		IP6K5 ⁷⁾		
	Connector version "C4"		IP6K6K ⁷⁾		
			IP6K9K ⁷⁾ (only with Rexroth type R901022127)		
	Connector version "K40"		IP6K7 and IP6K9K ⁷⁾		
Control electronics (separate order)			Valve amplifier for proportional valves type VT-SSPA1, data sheet 30116		
			Valve amplifier for proportional valves type VT-MSPA, data sheet 30232		
			Analog amplifier type RA, data sheet 95230		
			BODAS controller type RC, data sheets 95204, 95205, 95206		
Recommended dither frequency (PMW)		Hz	300		
Design according to VDE 0580					

Notice

For the electrical connection, a protective earth (PE $\overline{\text{N}}$) connection is mandatory based on the specification.

⁵⁾ Consult the manufacturer if planning to use > 2000 m above sea level.
⁶⁾ Due to the occurring surface temperatures of the solenoid coils, the standards ISO 13732-1 and ISO 4413 must be observed!


⁷⁾ With installed and locked plug-in connector. Plug-in connectors are not included in the scope of delivery and must be ordered separately, see data sheet 08006.

Characteristic curves

p - q_v flow characteristic curves


▼ Pressure at port P depending on flow

(The characteristic curves were measured without back-pressure at port T.)




▼ Minimum set pressure p_E at port P depending on flow when setpoint is 0

(The characteristic curve was measured without back-pressure at port T.)



p -I characteristic curves; flow = 10 l/min

▼ Pressure stage 420 bar




Notice

Characteristic curves measured with HLP46, $\vartheta_{oil} = 40 \pm 5$ °C and 24 V coil.


Permissible working range

Minimum terminal voltage on the coil and relative duty cycle depending on the ambient temperature

▼ Version “G12”




▼ Version “G24”



 = Limited valve performance

▼ Version "G12...-8"



 = Limited valve performance

Notice


The characteristic curves were determined for coils with valve for medium test block size (80 x 80 x 80 mm), w/o flow in still air.

Depending on installation conditions (block size, flow, air circulation, etc.) heat dissipation may be better. This increases the range of applications.

In specific instances, unfavorable conditions may limit the range of applications.

Dimensions

▼ KBVS.0A




- 1 Nut, tightening torque $M_A = 5+1$ Nm
- 2 WAF 24, tightening torque $M_A = 55+5$ Nm.
- 3 Plug-in connectors, separate order, see data sheet 08006
- 4 Space required to remove the plug-in connector
- 5 Device connector "K40"
- 6 Device connector "K4"
- 7 Device connector "C4"

- P** = Pump port
- T** = Tank port
- LS** = Location Shoulder

Mounting cavity

▼ R/C019E; 2 ports; 3/4-16UNF-2B thread




P = Pump port

T = Tank port

LS = Location Shoulder

Available individual components



Item	Denomination		DC voltage	Material number
	Coil for single connection ¹⁾	K4	12 V	R901002932
			24 V/1200 mA	R901002319
			24 V/800 mA	R901049962
		K40	12 V	R901003055
			24 V/1200 mA	R901003053
			24 V/800 mA	R901050010
		C4	12 V	R901003044
			24 V/1200 mA	R901003026
			24 V/800 mA	R901049963
990	Nut and seal ring for pole tube		R961010456	
998	Seal kit of the valve		R961011378	

1) Replacing the solenoid coil may result in a change of ±5% in the factory pressure setting.

Related documentation

- Control electronics:

– Valve amplifier for proportional valves

– Valve amplifier for proportional valves (Top hat rail assembly)

– Analog amplifier

– BODAS controller

type VT-SSPA1

type VT-MSPA

type RA

type RC

Data sheet 30116

Data sheet 30116

Data sheet 95230

Data sheets 95204, 95205, 95206
- Mineral oil-based hydraulic fluids

Data sheet 90220
- Environmentally acceptable hydraulic fluids

Data sheet 90221
- MTTF_D values

Data sheet 90294