

Strut profile 40x80L 2N

Technical data


Quick & Easy profile finishes

Standard profile finishes

Dimensions

40x80L 2N

$A = 10,9 \text{ cm}^2$
 $I_x = 66,6 \text{ cm}^4$
 $I_y = 20,8 \text{ cm}^4$
 $W_x = 16,6 \text{ cm}^3$
 $W_y = 10,4 \text{ cm}^3$
 $m = 2,9 \text{ kg/m}$



33093



Ordering codes

The following caps with holes are needed:

40x80 signal gray (1 item)

40x80 black (1 item)

The following cover caps are needed:

40x80 signal gray (1 item)

40x80 black (1 item)

	L			ESD	No.
	mm				
Strut profile 40x80L 2N	6070	12			3842555650
Strut profile 40x80L 2N Q&E	50 ... 6070		1		3842993768
Cover cap 40x80, signal gray			20		3842548748
Cover cap 40x80, black			20		3842548749
Cover cap with hole 40x80, signal gray			20		3842548788
Cover cap with hole 40x80, black			20		3842548789

Quick&Easy profile finishes

Standard profile finishes (note minimum length) ¹⁾	M12 / D9,8 / D17 / DB17 / F1 (A,D)
Customized profile finishes ($L_{\max} = 5400 \text{ mm}$) ²⁾	DI / DIS / MT / MTS / MI / MIS / DG

1) For the specified slots

2) $DG_{\max} = 45^\circ$; $L_{\min1} / L_{\min2} = 439 / 578 \text{ mm}$