

Strut profile 40x80L



Product description

[Quick & Easy profile finishes](#)

[Introduction to strut profiles](#)

Technical data

[Quick & Easy profile finishes](#)


Dimensions

Strut profile 40x80L

40x80L

$A = 9,9 \text{ cm}^2$
 $I_x = 63,4 \text{ cm}^4$
 $I_y = 17,3 \text{ cm}^4$
 $W_x = 15,9 \text{ cm}^3$
 $W_y = 8,7 \text{ cm}^3$
 $I_t = 8,02 \text{ cm}^4$
 $W_t = 4,8 \text{ cm}^3$
 $m = 2,7 \text{ kg/m}$

19210



Ordering codes

The following caps with holes are needed:

40x80 signal gray (1 item)

40x80 black (1 item)

The following cover caps are needed:

40x80 signal gray (1 item)

40x80 black (1 item)

	L			ESD	No.
	mm				
Strut profile 40x80L	50 ... 6070		1		3842993130
Strut profile 40x80L M12/-	60 ... 6000		1		3842993131
Strut profile 40x80L M12/M12	110 ... 6000		1		3842993132
Strut profile 40x80L D17/D17	80 ... 6000		1		3842993135
Strut profile 40x80L D17/D17V	80 ... 6000		1		3842993136
Strut profile 40x80L D17V/-	60 ... 6000		1		3842993137
Strut profile 40x80L D17V/D17V	80 ... 6000		1		3842993138
Strut profile 40x80L, 12xL=6070mm	6070	12			3842529341
Strut profile 40x80L Q&E	50 ... 6070		1		3842993728
Cover cap 40x80, signal gray			20		3842548748
Cover cap 40x80, black			20		3842548749

	L			ESD	No.
	mm				
Cover cap with hole 40x80, signal gray			20		3842548788
Cover cap with hole 40x80, black			20		3842548789
Strut profile 40x80L	6070		1		3842529342

Quick&Easy profile finishes

Standard profile finishes (note minimum length)		M12 / D9,8 / D17 / DB17 / F1 (A,D)
Customized profile finishes (L _{max} = 5400 mm) ¹⁾		DI / DIS / MT / MTS / MI / MIS / DG

1) DG_{max} = 45°; L_{min1} / L_{min2} = 439 / 578 mm