

Strut profile 40x30°



31 300

Product description

[Quick & Easy profile finishes](#)

[Introduction to strut profiles](#)

Technical data

[Quick & Easy profile finishes](#)


Dimensions

Strut profile 40x30°

40x30°

$A = 6,2 \text{ cm}^2$
 $I_x = 9,4 \text{ cm}^4$
 $I_y = 11,8 \text{ cm}^4$
 $W_x = 4,7 \text{ cm}^3$
 $W_y = 5,9 \text{ cm}^3$
 $I_t = 3,0 \text{ cm}^4$
 $W_t = 3,1 \text{ cm}^3$
 $m = 1,7 \text{ kg/m}$

19205



Ordering codes

The following cover caps can be used:

Cover cap 40x30°, signal gray (1x)

Cover cap 40x30°, black (1x)

	L			ESD	No.
	mm				
Strut profile 40x30°	50 ... 6070		1		3842993195
Strut profile 40x30° 12xL=6070	6070	12			3842529371
Strut profile 40x30° Q&E	50 ... 6070		1		3842993718
Cover cap 40x30°, black ESD			20		3842551015
Cover cap 40x30°, signal gray			20		3842551014
Strut profile 40x30°	6060		1		3842529372

Standard profile finishing Lmax = 6000 mm (note minimum length)		M12
---	--	-----