



Curve KE 1/O-90



- Curve direction right (KR = R) or left (KR = L)
- The installation location AO describes the installation situation on the curve infeed and outfeed.

- The drive takes place via a belt section BS 1/T connected to the curve output or the return unit UM 1 of a section unit.
- Using additional drive kits improves the transport of the workpiece pallets WT 1/P at the start and end of the curve.
- Conveyor medium: Round belt, suitable for use in an EPA

 Assembly instructions

Product description

Curve KE 1/O-90 without its own drive for 90° curve transport of a workpiece pallet.

Separation should be used to ensure that no accumulation occurs on the curve and on the overdrive belts.


Reversible operation is not possible.

Technical data


No.			3842999764	3842537618	3842537619
Max. section load in accumulation operation		kg	3		
ESD			yes		
Cleanroom class			ISO class 7		
Dry room	r.F.	%	< 1		

Dimensions

Curve KE 1/O-90



Ordering codes



31510

Order Parameter

b (mm)	Track width in the direction of transport	80; 120; 160
KR	Curve direction R: right L: left	L; R
AO	Installation location Installation location at start/end of curve	A; B; C; D

	No.
Curve KE 1/O-90	3842999764
Drive kit AS 1	3842537618
Drive kit BS 1	3842537619