


Strut profile 22.5x45



Product description

[Quick & Easy profile finishes](#)

[Introduction to strut profiles](#)

Technical data


[Quick & Easy profile finishes](#)

Dimensions

Strut profile 22.5x45

22,5x45

$A = 4,7 \text{ cm}^2$
 $I_x = 7,1 \text{ cm}^4$
 $I_y = 2,9 \text{ cm}^4$
 $W_x = 3,2 \text{ cm}^3$
 $W_y = 2,6 \text{ cm}^3$
 $m = 1,3 \text{ kg/m}$



19452

Ordering codes

The following cover caps are needed:

22.5x45 signal gray (1 item)

22.5x45 black (1 item)

	L			ESD	No.
	mm				
Strut profile 22.5x45 D17V/D17V	50 ... 6070		1		3842990292
Strut profile 22.5x45	60 ... 6000		1		3842990087
Strut profile 22.5x45 M12/-	110 ... 6000		1		3842990090
Strut profile 22.5x45 M12/M12	80 ... 6000		1		3842990091
Strut profile 22.5x45, 24xL=6070mm	6070	24			3842537812
Strut profile 22.5x45 Q&E	50 ... 6070		1		3842993700
Cover cap 22.5x45, signal gray			20		3842548830
Cap 22.5x45, black			20		3842548831

Standard profile finishing Lmax = 6000 mm (note minimum length) ¹⁾	M12 / D9,8 (A,C)1) / D17 / DB17 (A,C)
Individual profile finishing (L _{max,l} = 5400 mm) ²⁾	DI / DIS / MT / MTS / MI / MIS / DG

1) For the specified slots

2) $DG_{max} = 45^{\circ}$; $L_{min1} / L_{min2} = 378 / 456$ mm